## $Selected\ Questions-Set\ 7-Answers$

1.

| Qı | iest | tion  | Expected Answers  |    | Additional Guidance   |  |
|----|------|-------|---|----|---|--|
|    | а    | (i)   | uniformly spaced, vertical parallel lines must<br>begin and end on the plates with a minimum of                           |    | ignore any edge effects   |  |
|    |      |       | three lines   | B1 |   |  |
|    |      |       | arrow in the correct direction down   | B1 |   |  |
|    |      | (ii)  | $E = V / d$ $E = 60 / 5 \times 10^{-3}$<br>= 12000 (V m <sup>-1</sup> )   | A1 |   |  |
|    | b    | (i)   | Use of energy qV and kinetic energy = ½ mv <sup>2</sup>   | M1 |   |  |
|    |      |       | $v = [(2qV)/m]^{1/2}$   |    |   |  |
|    |      |       | $v = [(2 \times 3.2 \times 10^{-19} \times 400)/6.6 \times 10^{-27}]^{1/2}$   | M1 |   |  |
|    |      |       | $v = 1.97 \times 10^5 \text{ (m s}^{-1}\text{)}$  | A0 |   |  |
|    |      | (ii)  | a = F / m a = Eq / m  | C1 | Both required for the mark  |  |
|    |      |       | $a = (12000 \times 3.2 \times 10^{-19}) / 6.6 \times 10^{-27})$   |    |   |  |
|    |      |       | = 5.82 x 10 <sup>11</sup> (m s <sup>-2</sup> )  | A1 |   |  |
|    |      | (iii) | 1 $t = (16 \times 10^{-3}) / 2 \times 10^{5}$   | M1 | Answer will depend on number of sf used by candidate.                     |  |
|    |      |       | = 8 x 10 <sup>-8</sup> (s)  | A0 |   |  |
|    |      |       | 2  s = $\frac{1}{2}$ a x t <sup>2</sup> = $\frac{1}{2}$ [5.82 x 10 <sup>11</sup> x (8 x 10 <sup>-8</sup> ) <sup>2</sup> ] | C1 | Using u = 2 x 10 <sup>5</sup> scores 0/2                                  |  |
|    |      |       | = 1.86 x 10 <sup>-3</sup> (m)   | A1 | Allow slight variation in answers that follow from the candidates working |  |

| Question | Answers  | Additional Comments/Guidance   | Mark  |
|----------|--|--|-------|
| (a)      | force between two (point) charges is  proportional to product of charges ✓ inversely proportional to square of distance between the charges ✓  | Mention of force is essential, otherwise no marks. Condone "proportional to charges". Do not allow "square of radius" when radius is undefined. Award full credit for equation with all terms defined.   | 2     |
| (b)      | V is inversely proportional to r [or V ∞ (-)1/r] ✓  (V has negative values) because charge is negative  [or because force is attractive on + charge placed near it  or because electric potential is + for + charge and – for – charge] ✓  potential is defined to be zero at infinity ✓   | Allow $V \times r = \text{constant for 1}^{\text{st}} \text{ mark}$  | max 2 |
| (c)(i)   | $Q(=4\pi\varepsilon_0 rV) = 4\pi\varepsilon_0 \times 0.125 \times 2000$ (for example, using any pair of values from graph) $\checkmark$ = 28 (27.8) ( ± 1) (nC) $\checkmark$   | or gradient = Q/4πε <sub>0</sub> = 2000/8 ✓<br>(gives Q = 28 (27.8) ±1 (nC) ✓  | 2     |
| (c)(ii)  | at $r = 0.20$ m $V = -1250$ V and at $r = 0.50$ m $V = -500$ V so pd $\Delta V = -500 - (-1250) = 750$ (V) $\checkmark$ work done $\Delta W$ (= $Q\Delta V$ ) = $60 \times 10^{-9} \times 750$ = $4.5(0) \times 10^{-5}$ (J) (45 $\mu$ J) $\checkmark$ (final answer could be between 3.9 and $5.1 \times 10^{-5}$ )   | Allow tolerance of $\pm$ 50V on graph readings. [Alternative for 1 <sup>st</sup> mark: $\Delta V = \frac{27.8 \times 10^{-9}}{4\pi \varepsilon_0} \times \left(\frac{1}{0.2} - \frac{1}{0.5}\right) \text{ (or similar substitution using 60 nC instead of 27.8 nC: use of 60 nC gives } \Delta V = 1620V) ]}$ | 2     |
| (c)(iii) | $E\left(=\frac{Q}{4\pi\varepsilon_0 r^2}\right) = \frac{27.8 \times 10^{-9}}{4\pi\varepsilon_0 \times 0.40^2}  \checkmark = 1600 \text{ (1560) (V m}^{-1})  \checkmark$ [or deduce $E = \frac{V}{r}$ by combining $E = \frac{Q}{4\pi\varepsilon_0 r^2}$ with $V = \frac{Q}{4\pi\varepsilon_0 r}$ \leftilde{from graph } $E = \frac{625 \pm 50}{0.40} = 1600 \text{ (1560 \pm 130) (V m}^{-1})  \checkmark$ ] | Use of Q = 30 nC gives 1690 (V m <sup>-1</sup> ).  Allow ecf from Q value in (c)(i).  If Q = 60 nC is used here, no marks to be awarded.   | 2     |

3.

| а | i  | required pd ( = $2.5 \times 10^6 \times 12 \times 10^{-3}$ ) = $3.0(0) \times 10^4$ (V) $\checkmark$   | 1 |  |
|---|----|--|---|--|
|   |    |  |   |  |
| а | ii | charge required $Q = CV = 3.7 \times 10^{-12} \times 3.00 \times 10^4 \checkmark$<br>$(= 1.11 \times 10^{-7} \text{ C})$<br>time taken $t = \frac{Q}{I} = \frac{1.11 \times 10^{-7}}{3.2 \times 10^{-8}} = 3.5 (3.47) \text{ (s) } \checkmark$ | 2 | Allow ECF from incorrect $\mathcal V$ from (a)(i).             |
| b | i  | time increases $\checkmark$ (larger $C$ means) more charge required (to reach breakdown pd) $ \mathbf{or} \ \ t = \frac{CV}{I} \qquad \mathbf{or} \qquad \text{time} \propto \text{capacitance} \ \checkmark $                                 | 2 | Mark sequentially i.e. no explanation mark if effect is wrong. |
|   |    |  |   |  |
| b | ii | spark is brighter (or lasts for a longer time) ✓ more energy (or charge) is stored or current is larger or spark has more energy ✓   | 2 | Mark sequentially.   |

| Answers   | Additional comments/Guidelines  | Mark |
|---|---|------|
| $V = V_0 \left( 1 - e^{-\frac{t}{RC}} \right)$ with substitution attempted with $V_0$ being larger than $V \checkmark_1$  | NB The answer can be obtained incorrectly by finding the time to charge to 2V using a 4V supply. This approach may only gain the first mark for an attempted use of the equation. | 3    |
| Time to charge to 4.0 V = $t_2 = -R_1C \ln\left(1 - \frac{4}{6}\right)$ OR  | Award 0 for a solution using the discharge equation.  |      |
| Time to charge to 2.0 V = $t_1 = -R_1C \ln\left(1 - \frac{2}{6}\right) \checkmark_2$  | Condone R for R <sub>1</sub>  |      |
|   | ✓ 2 If given in an equation then then time must be the subject or be in a form that is used to obtain mp3   |      |
| $t = t_2 - t_1 = -R_1 C \ln\left(\frac{1}{3}\right) - \left\{-R_1 C \ln\left(\frac{2}{3}\right)\right\}$  | can be awarded for $t_2 = 1.10 \times R_1 C$ <b>OR</b> $t_1 = 0.41 \times R_1 C$  |      |
| $ \left( = -R_1 C \left( \ln \frac{1}{3} - \ln \frac{2}{3} \right) = -R_1 C \ln \left( \frac{1}{3} \right) \right) = -R_1 C \ln \left( \frac{1}{2} \right) = 0.69 R_1 C $ | <b>D</b>  |      |
|   | √ <sub>3</sub> Must see 0.69 <i>R</i> <sub>1</sub> <i>C</i> for 3 marks.  |      |
| OR<br>= $R_1 C (1.10 - 0.41) = 0.69 R_1 C \checkmark_3$   | Only award MP3 for $0.69R_1C$ if the solution involves a time difference.   |      |

| Answers   | Additional comments/Guidelines  | Mark |
|---|---|------|
| Attempt to find usable data from <b>Figure 9</b> ✓ <sub>1</sub>   | Method 2 (from individual data points)  | 4    |
| Determine scaling factor <b>OR</b> Determine $R_1 \checkmark_2$   | Possible methods are shown but only final answers   |      |
| Calculate $Q$ the charge stored at $4~{\rm V}$ or the charging time constant from a valid method $\checkmark_3$   | requested are needed to gain marks.  ✓ 1b Use of a current and voltage across the resistor, |      |
| Determine $C$ to a value that rounds to $1 \times 10^{-4}$ (F) to 2 or more sf (expect to see $1.0 \times 10^{-4}$ F) $\checkmark_4$                      | e.g. $I = 2.0 \times 10^{-5}$ A and voltage across resistor = 2 V (when capacitor has 4 V)  |      |
|   | OR  |      |
| Method 1 (from area)  | $I = 6.0 \times 10^{-5}$ A and voltage across resistor = 6 V (when capacitor has 0 V)       |      |
| √ <sub>1a</sub> Attempt at finding area under <i>I</i> − <i>t</i> graph by counting boxes   | $\checkmark_{2b} R_1 = \frac{V}{I} = \frac{2.0}{2.0 \times 10^{-5}}$                        |      |
| $\checkmark_{2a} \ 1 \ cm^2$ box corresponds to charge $0.5 \times 10^{-5} \ C$   | 1 2.0×10  |      |
| $✓_{3a}$ Number of 1 cm <sup>2</sup> boxes = 80 (78 to 82)  | OR $\left(\frac{V}{I} = \frac{6}{6 \times 10^{-5}}\right) = 1.0 \times 10^{5} \ (\Omega)$   |      |
| $Q = (80 \times 0.5 \times 10^{-5}) = (3.9 \text{ to } 4.1) \times 10^{-4} \text{ (C)}$ their $Q$ = 3 yelve that rounds to 1 × 10 <sup>-4</sup> (E) (> 2) | $✓$ <sub>3b</sub> Charging time constant = $R_1C$   |      |
| $\checkmark_{4a} C = \frac{\text{their } Q}{4} = \text{a value that rounds to } 1 \times 10^{-4} \text{ (F) } (\ge 2 \text{ sf required)}$                | Eg using $I = I_0 e^{\frac{-t}{R_1 C}}$ then $R_1 C = \frac{t}{\ln(\frac{I_0}{I})}$         |      |
| Award MAX 1 for estimating the average current by sight   | Substituting $I = 2 \times 10^{-5}$ A and   |      |
| and using $C = \frac{IT}{V}$ .  | $I_0 = 6 \times 10^{-5} \text{ A} \text{ and } t = 11 \text{ s}.$                           |      |
| , , , , , , , , , , , , , , , , , , ,   | OR  |      |
|   | Graphical method must include evidence from Figure 9  |      |
|   | charging time constant $(R_1C) = 10.(0)$ (s)  |      |
|   | $\checkmark_{4b} C = \frac{\text{time constant}}{R_1} = \frac{10.0}{1.0 \times 10^5}$       |      |
|   | = a value that rounds to 1 × 10 <sup>-4</sup> (F) (≥ 2 sf required)                         |      |

| Answers   | Additional comments/Guidelines  | Mark |
|---|---|------|
| Reading of relevant discharge data from Figure 10 provided there is an attempt to use data ✓₁                   | √₁ From Figure 10 this can be the time taken for the voltage to fall to half its value.   | 3    |
| A valid substitution of their data into a relevant equation to find $R_1$ or $R_{\text{Total}} \checkmark_2$    | ✓ <sub>2</sub> Finding $R_{\text{Total}}$ from <b>Figure 10</b><br>4.0 V to 2.0 V in (32 – 11) s using $t_{\underline{1}} = 0.69RC$ allow = $0.7RC$ |      |
| $R_2 = R_{\text{Total}} - \text{their } R_1 = 2.0 \times 10^5 \ \Omega \ \checkmark_3$                          | $R_{\text{Total}} = 3.0 \times 10^5 \Omega$   |      |
| allow <b>one</b> ecf from either their $R_{Total}$ <b>or</b> their $R_1$  | Terotal Crown In The  |      |
| When $R_1$ is derived in an earlier question accept<br>this value of $R_1$ and allow ecf for $R_{\text{total}}$ | Finding R <sub>1</sub> from <b>Figure 9</b> 6.0 A to 3.0 A in 6.8 s using   |      |
| When $R_1$ is derived in this question, allow one ecf from either their $R_{\text{total}}$ or their $R_1$       | $t_{\frac{1}{2}} = 0.69RC \text{ allow} = 0.7RC$<br>$R_1 = 1.0 \times 10^5 \Omega$  |      |
|   | OR  |      |
|   | Using   |      |
|   | $I = I_o e^{\frac{-\tau}{R_i C}}$   |      |
|   | for example, with $I = 2 \times 10^{-5}$ A and $I_0 = 6 \times 10^{-5}$ A and $t = 11$ s  |      |
|   | Note R <sub>1</sub> may be taken from <b>05.2</b> and not use the graph information.  |      |

| Question | Answers   | Additional Comments/Guidelines   | Mark |
|----------|---|--|------|
| (a)      | (using mass defect = $\Delta m = Z m_p + N m_n - M_{Co}$ )<br>$\Delta m = 27 \times 1.00728 + 32 \times 1.00867 - 58.93320$ (u) $\checkmark$<br>$\Delta m = 0.5408$ (u) $\checkmark$<br>Binding Energy = $0.5408 \times 931.5 = 503.8$ (MeV) $\checkmark$ (CE this mark stands alone for the correct energy conversion even if more circular routes are followed.                   | Look at use of first equation and if electrons are used or mass of proton and neutron confused score = 0. If subtraction is the wrong way round lose 1 mark. Data may come from rest mass eg m <sub>n</sub> =939.551 MeV or $1.675 \times 10^{-27}$ kg or $1.00867$ u. So if kg route used $\Delta m = 8.83 \times 10^{-28}$ kg BE = $7.95 \times 10^{-28}$ J and 497 MeV. Conversion mark ( $2^{\text{nd}}$ ) may come from a wrong value worked through. $0.47(5)$ | 3    |
| (b)      | $(2.52 - 1.76) \times 10^{-13} = 7.6 \times 10^{-14} \text{ J} \checkmark$<br>$7.6 \times 10^{-14} / 1.60 \times 10^{-13} = 0.47 \text{ or } 0.48 \text{ MeV} \checkmark (0.475 \text{ MeV})$   | Correct answer scores both marks.  | 2    |
| (c)      | 6 (specific wavelengths)  |  | 1    |
| (d)      | (longest wavelength = lowest frequency = smallest energy) $ (2.29 \times 10^{-13} - 2.06 \times 10^{-13}) = 2.3 \times 10^{-14} \text{ (J)} \checkmark $ $ \lambda (= h \text{ c / E}) = 6.63 \times 10^{-34} \times 3.00 \times 10^8 \text{ / } 2.3 \times 10^{-14} \checkmark $ $ \lambda = 8.6 - 8.7 \times 10^{-12} \text{ (m)} \checkmark (8.6478 \times 10^{-12} \text{ m}) $ | Allow a CE in the second mark only if the energy corresponds to an energy gap including those to the ground state.  The allowed energy gaps for CE are: 2.29, 2.06, 1.76, 0.53, 0.30 all x 10 <sup>-13</sup> J  Note substitution rather than calculation gains mark.  The final mark must be as shown here and not from a CE above.   | 3    |

| Question | Expected Answers  | Marks        | Additional Guidance   |
|----------|---|--------------|---|
| a        | ANY ONE from X-rays interact with matter by: the photoelectric effect where an (orbital) electron is ejected from atom / atom is ionised  Compton scattering where X-ray scattered by the interaction with (orbital) electron  Pair production where X-ray photon interacts with the nucleus / atom and an electron and positron are produced  [allow one mark for statement and one for explanation] | (B2)<br>(B2) | Allow electrons ejected from metal surface if reference is made to <u>free</u> electrons  Allow: X-ray diffraction B1  X-ray passes through the 'slits' / atomic gap formed by the atoms B1 |
|          | Max 2   | B2           |   |

| b |     | $I = I_0 e^{-\mu x}$ $0.1 = e^{-\mu 3}$  | C1   | Calculation of μ =0.768 C1   |
|---|-----|--|------|--|
|   |     | $0.5 = e^{-\mu x}$   |      | Substitution into second equation C1   |
|   |     | In 0.5 / In0.1 = x/3   | C1   |  |
|   |     | x = 0.903 (mm)   | A1   | Allow 0.9 (1sf)  |
|   |     |  |      | If question misread and 0.9 used for change $\mu$ = 0.035 and x = 19.7 (allow 20) give 2/3 |
|   |     |  |      |  |
| С | (i) | Absorption of X-rays by (silver halide molecules) by a photographic film                         | (B1) |  |
|   |     | Uses of fluorescent / scintillator/ phosphor   | (B1) |  |
|   |     | Photon releases electron (that is accelerated onto a fluorescent screen)                         | (B1) |  |
|   |     | number of electrons increased /multiplied  | (B1) |  |
|   |     | MAX B2   | B2   |  |
|   |     | QWC: Phosphor / Intensifier/ it converts X-ray photon into increased number of 'visible' photons |      |  |
|   |     |  | B1   |  |

|  | (ii) | Different <u>soft</u> body <u>tissue</u> produce little difference in contrast/attenuation           | (B1) | This method produces good contrast for soft tissue /for similar Z values |
|--|------|--|------|--|
|  |      | (Contrast media with) high atomic number / Z used / iodine or barium (used to give greater contrast) | (B1) |  |
|  |      | liquids injected or swallowed into soft tissue areas / or examples of such                           | (B1) |  |
|  |      | MAX B2   | B2   |  |